

FireSafe FD30S Glazed Flat Entrance Doorsets



SPECIFICATION

Door Leaf Type:	Solid timber core with SMC external and PVCu internal facings
Outer Frame Type:	PVCu extrusion
Frame Reinforcement:	Engineered hardwood
Intumescent Seal Locations:	Top & bottom of door leaf, outer frame rebate & outside edge, & around selected components
Threshold:	Low level 'Part M' compliant mobility threshold OR 3mm air gap
Timber Cill Options:	None, 12x80, 30x95, 45x95, 30x144 or 45x144
Locks:	ERA Surefire 4-point autofire locking system with adjustable keeps Fullex SL16 Crimebeater 4-point slam shut autolock with adjustable keeps
Hinges:	4no. steel butt hinges
Cylinder:	TS007 3 Star Key-thumbturn cylinder (3 keys)
Handles:	Lever/lever
Viewer:	TS002 fire rated viewer (optional)
Knocker:	Urn knocker (optional)
Letterplate:	TS008 fire rated letterplate with integral internal security cowl (optional)
Closers:	Rutland TS.5204 scissor arm overhead closer Rutland TS.11204 slide arm overhead closer Fireco Freedor free-swing overhead closer
Security Chain:	TS003 security chain (optional)
Numerals:	75mm (optional)
Hardware Finish:	Anodised Gold or Silver Polished Gold or Chrome
Glazing system:	Flush glazed with trims internally only
Glass type:	Pyrobelite/laminated or Pyronova/laminated clear or Stippolyte double glazed units
Toplight Glass:	Pyrobelite/laminated or Pyronova/laminated clear or Stippolyte double glazed units (Min height 260mm, Max height 400mm)

CERTIFICATION AND ACCREDITATION

Fire resistance tested to:	BS 476-20 & 22:1987 BS EN 1634-1:2014+A1:2018
Smoke Control tested to:	BS EN 1634-3:2004
Bi-directional fire & smoke testing:	All doorset styles are bi-directionally tested
3rd Party Certification:	IFC Certification Ltd SDP01 Fire Doorset Certification Scheme
UKCA Marking:	External – Yes Internal – Not required
Enhanced Security:	PAS 24
Dual Certification:	Fire resistant/enhanced security doorsets with Bluesky Certification
Secured By Design:	Secured by Design accredited

Sizes available (exc cill and add-ons)

Min 833 to 1921mm

Max 1012 to 2115mm

Hardwood add-ons available in sizes 15mm, 25mm and 50mm

DOOR COLOUR OPTIONS – EXTERNAL FACE

